

# CE200 CQB + SONE

**Product Definition**

Tufted Patterned Structured Loop Pile

**Pile Material**

100% Recycled Solution Dyed Nylon

**Pile Yarn Weight**

747 g/m<sup>2</sup> ± 5%

**Total Weight**

4,094 g/m<sup>2</sup> ± 5%

**Effective pile yarn weight**

XX g/m<sup>2</sup> ± 10%

**Pile Height**

4.0 mm ± 0.5 mm

**Total Thickness**

10.2 mm +15% / - 10%

**Gauge/Ends 10 cm**

1/10 - 39.4

**Tufts per m<sup>2</sup>**

190,395 ± 5%

**Backing Type**

CQuestBio SONE

**Wear Classification**

EN 1307 33 Heavy Contract LC2

**Radiant Panel**

(EN ISO 9239/1 Euroclass\_Bfl s1 (EN ISO 13501))

**Dimensional Stability**

≤ 0.2% ( EN 986)

**Impact Sound Insulation (ΔL<sub>w</sub>)**

28 dB (EN ISO 10140-3)

**Rating of Sound Absorption**



0.30 (EN ISO 11654)








**Sound Absorption**



|                      |                      |                      |                       |                       |                       |                                |
|----------------------|----------------------|----------------------|-----------------------|-----------------------|-----------------------|--------------------------------|
| <b>125Hz</b><br>0.02 | <b>250Hz</b><br>0.05 | <b>500Hz</b><br>0.34 | <b>1000Hz</b><br>0.29 | <b>2000Hz</b><br>0.35 | <b>4000Hz</b><br>0.53 | (EN ISO 354)<br>α <sub>s</sub> |
|----------------------|----------------------|----------------------|-----------------------|-----------------------|-----------------------|--------------------------------|




**Style 4316**

3m<sup>2</sup> - 20Tiles per Box (50 cm x 50 cm ± 0.2%)

|  |  |
|--|--|
| <br>DOP:<br>EN 14041:2004<br>Notified Body - 0493<br>COC<br>0493/CPR/0181<br>For use as floor covering in buildings | <br>DOP:<br>EN 14041:2004<br>Approved Body - 8515<br>COC<br>8515/CPR/0181<br>For use as floor covering in buildings |
|--|--|

|   |   |   |   |   |  |   |
|---|---|---|---|---|--|---|
|  |  |  |  |  |  |  |
| <input checked="" type="checkbox"/>   | <input type="checkbox"/>  | <input type="checkbox"/>  | <input type="checkbox"/>  | <input type="checkbox"/>  | <input type="checkbox"/>   | <input type="checkbox"/>  |

|  |   |
|--|---|
|  |  |
| <input type="checkbox"/>   | <input type="checkbox"/>  |

|   |   |  |
|---|---|--|
|  |  |  |
| <input checked="" type="checkbox"/>   | <input type="checkbox"/>  | <input type="checkbox"/>   |
| <input type="checkbox"/> BFL on request   |   |  |



|  |   |   |   |
|--|---|---|---|
|  |  |  |  |
|--|---|---|---|

|  |   |   |   |   |
|--|---|---|---|---|
|  |  |  |  |  |
|--|---|---|---|---|





**Carbon Footprint / m<sup>2</sup> (Cradle to Gate)\***

**Total Recycled Content & Biobased Contents**

**Total Virgin Content**

**Yarn Recycled Content**

LRVs (link to sharepoint location):

**Other Comments**

Interface European Manufacturing BV reserves the right to change or modify specifications. Please see website for latest specifications: [www.interface.com](http://www.interface.com)

Date 30/09/24