

Ice Breaker CQB + SONE+

Product Definition

Tufted Patterned Structured Loop Pile

Pile Material

100% Solution Dyed Nylon contains recycled content

Pile Yarn Weight

616 g/m² ± 5%

Total Weight

4,260 g/m² ± 5%

Effective pile yarn weight

XX g/m² ± 10%

Pile Height

3.7 mm ± 0.5 mm

Total Thickness

10.1 mm +15% / - 10%

Gauge/Ends 10 cm

1/12 – 47.2

Tufts per m²

190,130 ± 5%

Backing Type

CQuestBio SONE+

Wear Classification

EN 1307 33 Heavy Contract

LC2

Radiant Panel

(EN ISO 9239/1 Euroclass Bfl s1 (EN ISO 13501))

Dimensional Stability

≤ 0.2% (EN 986)

Impact Sound Insulation (ΔL_w)

33 dB (EN ISO 10140-3)

Rating of Sound Absorption



0.35 (EN ISO 11654)








Sound Absorption


125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	(EN ISO 354) α _s
0.03	0.08	0.43	0.27	0.35	0.54	

Style 4282

3m² - 12Tiles per Box (50 cm x 50 cm ± 0.2%)

 DOP: EN 14041:2004 Notified Body - 0493 COC 0493/CPR/0181 For use as floor covering in buildings	 DOP: EN 14041:2004 Approved Body - 8515 COC 8515/CPR/0181 For use as floor covering in buildings
---	---

						
<input checked="" type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>



BFL on request



Carbon Footprint / m² (Cradle to Gate)*

Total Recycled Content & Biobased Contents

Total Virgin Content

Yarn Recycled Content

LRVs (link to sharepoint location):

Other Comments

Interface European Manufacturing BV reserves the right to change or modify specifications. Please see website for latest specifications:

Date 26/09/24

www.interface.com