

















Recreation CQB + SONE

Product Definition	Tufted Patterned Structured Loop Pile
Pile Material	100% Recycled Solution Dyed Nylon
Pile Yarn Weight	583 g/m ² ± 5%
Total Weight	3,905 g/m ² ± 5%
Effective pile yarn weight	XX g/m ² ± 10%
Pile Height	2.8 mm ± 0.5 mm
Total Thickness	8.6 mm +15% / - 10%
Gauge/Ends 10 cm	1/12 - 47.2
Tufts per m²	162,840 ± 5%
Backing Type	CQuestBio SONE
Wear Classification	EN 1307 33 Heavy Contract LC2

Radiant Panel	(EN ISO 9239/1 Euroclass Bfl s1 (EN ISO 13501)
Dimensional Stability	≤ 0.2% (EN 986)
Impact Sound Insulation (ΔL_w)	28 dB (EN ISO 10140-3)
Rating of Sound Absorption	0.30 (EN ISO 11654)

Sound Absorption						
125Hz	250Hz	500Hz	1000Hz	2000Hz	4000Hz	(EN ISO 354)
0.02	0.05	0.34	0.29	0.35	0.53	α _s

Style 4313 3m2 - 12Tiles per Box (50 cm x 50 cm ± 0.2%)

 <p>DOP: EN 14041:2004 Notified Body - 0493</p> <p>COC 0493/CPR/0181</p> <p>For use as floor covering in buildings</p>	 <p>DOP: EN 14041:2004 Approved Body - 8515</p> <p>COC 8515/CPR/0181</p> <p>For use as floor covering in buildings</p>	 Non Directional <input checked="" type="checkbox"/>	 Brick <input type="checkbox"/>	 Quarter Turn <input type="checkbox"/>	 Ashlar <input type="checkbox"/>	 Monolithic <input type="checkbox"/>	 Skinny Planks Ashlar <input type="checkbox"/>	 Skinny Planks Herringbone <input type="checkbox"/>
								
		<input checked="" type="checkbox"/> BFL on request						
								

Carbon Footprint / m² (Cradle to Gate)*
Total Recycled Content & Biobased Contents
Total Virgin Content
Yarn Recycled Content

LRVs (link to sharepoint location):

Other Comments

Interface European Manufacturing BV reserves the right to change or modify specifications. Please see website for latest specifications: www.interface.com

Date 25/09/24