NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING 130 CARPET TILING

A Cut Above

NSSPlus

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	A Cut Above
Туре	Tapestry Tufted Patterned Structured Tip Sheared Pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classific	ation
Category	Туре 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC3
Total Thickness	9.1 mm ± 0.5 mm
Size	100 x 100 cm standard size
Colourway	7274010 Amber 7274011 Carnation 7274012 Leather 7274013 Sienna 7274014 Pacific
Method of laying	Non-Directional Install using TacTiles [®] for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities). All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click <u>here</u> For Installation instructions, click <u>here</u> For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

Interface[®]