

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Connected Ethos - CE100

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Connected Ethos - CE100			
Туре	Tufted Patterned Structured Loop Tile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classific	ation			
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	6.4 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	4314001 Connect	4314002 Gaze	4314003 Explore	4314004 Observe
	4314005 Evolve	4314006 Consider	4314007 Expose	4314008 Reveal
	4314009 Awake	4314010 Emulate	4314011 Perceive	4314012 Identify
	4314013 Distinguish	4314014 Survey	4314015 Create	4314016 Affirm
	4314017 Contend	4314018 Confirm	4314019 Sustain	4314020 Captivate
	4314021 Encounter	4314022 Search	4314023 Shade	4314024 Uncover
	4314025 Unearth	4314026 Breathe	4314027 Embody	4314028 Escape
	4314029 Embark	4314030 Enchant	4314031 Exist	4314032 Scenic
Method of laying	Non Directional Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here



