

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Connected Ethos - CE200

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.		
Base	Please refer to Interface installation guide for details of suitability.		
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.		
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.		
Carpet Tiles			
Manufacturer	Interface		
Product Reference	Connected Ethos - CE200		
Туре	Tufted Patterned Structured Loop Tile		
Yarn	100% Recycled Solution Dyed Nylon		
Standard Backing	CQuest™Bio		
BS EN 1307 classification			
Category	Type 1		
Level of use class	Heavy Contract, class 33		
Luxury rating class	LC2		
Total Thickness	7.5 mm ± 0.5 mm		
Size	50 x 50 cm standard size		
Colourway	4316001 Perceive/Identify	4316002 Emulate/Perceive	4316003 Observe/Reveal
	4316004 Expose/Affirm	4316005 Survey/Expose	4316007 Create/Sustain
	4316008 Emulate/Encounter	4316009 Observe/Uncover	4316010 Survey/Contend
	4316011 Consider/Escape	4316012 Evolve/Shade	4316013 Consider/Survey
Method of laying	Non Directional Install using TacTiles® for a glue-free installation		

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

