

## NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Fresco Valley - Cliff

Location	Heavy use for entrance and stairs in office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface LVT installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Luxury Vinyl Tiles	
Supplier	Interface
Product Reference	Fresco Valley - Cliff
Туре	High performance luxury vinyl tile with Ceramor+ coating, PTV 36+ wet
Standard Backing	Sound Choice™ acoustic backing
BS EN 651 classification	
Category	Heterogeneous luxury vinyl tile
Level of use class	Class 33 heavy commercial / 42 general light industrial
Total Thickness	4.5 mm ± 0.5 mm
Size	25 x 100 cm standard size
Colourway	A02401 Lapis A02402 Sandstone A02403 Limestone A02404 Alabaster A02405 Granite A02406 Ironstone
Method of laying	Ashlar, Herringbone

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

For Installation instructions, click <u>here</u>
For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

