

Haptic

| | | | |
|----------------------------------|-----------------------------------------------------------------------------------------------------------|----------------|--------------|
| Location | Heavy use areas. Office, retail, hospitality, leisure and educational areas. | | |
| Base | Please refer to Interface installation guide for details of suitability. | | |
| Preparation | Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. | | |
| Fabricated Underlay | N/a. Carpet tiles to be adhered direct to the subfloor. | | |
| Carpet Tiles | | | |
| Manufacturer | Interface | | |
| Product Reference | Haptic | | |
| Type | Tapestry Tufted Patterned Structured Loop Pile | | |
| Yarn | 100% Recycled Solution Dyed Nylon | | |
| Standard Backing | CQuest™Bio | | |
| BS EN 1307 classification | | | |
| Category | Type 1 | | |
| Level of use class | Heavy Contract, class 33 | | |
| Luxury rating class | LC2 | | |
| Total Thickness | 6.9 mm ± 0.5 mm | | |
| Size | 25 x 100 cm standard size | | |
| Colourway | 9274021 Whisper | 9274022 Balsam | 9274023 Lace |
| Method of laying | Ashlar & Herringbone Install using TacTiles® for a glue-free installation | | |

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465