

Heuga 580 II

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Heuga 580 II			
Type	Tufted Plain Level Loop Pile			
Yarn	100% Recycled Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	5.8 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	1267225 Nickel	1267226 Elephant	1267229 Oyster	1267232 Onyx
	1267233 Zircon	1267234 Earth	1267236 Black	1267237 Quartz
	1267239 Rosewood	1267240 Timber	1267244 Wenge	1267245 Canary
	1267246 Cantaloupe	1267250 Flamingo	1267253 Lavender	1267257 Leak Blue
	1267259 Blue Moon	1267260 Blueberry	1267262 Deep River	1267265 Laurel
	1267268 Windsor Green	1267270 Pear	1267271 The Shire	1267274 Reef
Method of laying	Monolithic, Quarter Turn Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465