NBS



Hydropolis

NSSPlus

1	
Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Hydropolis
Туре	Tufted Patterned Textured Loop Pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classific	ation
Category	Туре 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC3
Total Thickness	7.0 mm ± 0.5 mm
Size	50 x 50 cm standard size
Colourway	4236008 Magenta 4236009 Tangerine 4236009 Tangerine 4236011 Emerald 4236012 Cobalt
Method of laying	Non Directional & Ashlar Install using TacTiles [®] for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities). All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

Interface[®]