



Net Effect B603

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Net Effect B603
Type	Tapestry Tufted Patterned Structured Loop Pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	7.3 mm ± 0.5 mm
Size	50 x 50 cm - 4 m ² Box
Colourway	7418001 Black Sea 7418002 North Sea 7418003 Pacific 7418004 Arctic 7418005 Atlantic 7418006 Caspian 7418007 Sand 7418008 Driftwood
Method of laying	Non Directional. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465