NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING 130 CARPET TILING

Brushed Lines

NSSPlus

Location	Heavy use for entrance and stairs in office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface LVT installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Luxury Vinyl Tiles				
Supplier	Interface			
Product Reference	Brushed Lines			
Туре	High performance luxury vinyl tile			
Standard Backing	Sound Choice™ acoustic backing			
BS EN 651 classifica	tion			
Category	Heterogeneous luxury vinyl tile			
Level of use class	Class 33 heavy commercial / 42 general light industrial			
Total Thickness	4.5 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	A01601 Talc A01605 Graphite A01610 Bisque A01614 Honey A01618 Celadon	A01611 Mousse	A01603 Mist A01607 Powder A01612 Soft Shadow A01616 Rouge A01621 Arbella	A01604 Galena A01608 Sandalwood A01613 Blush A01617 Dew A01622 Deep Cobalt
Method of laying	Ashlar and Herringbone			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

For Installation instructions, click <u>here</u> For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

Interface[®]