

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Composure

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Composure			
Туре	Tufted Patterned Structured Loop Pile			
Yarn	100% Solution Dyed Nylon contains recycled content			
Standard Backing	CQuest™Bio			
Backing Options	SONE®			
BS EN 1307 classific	cation			
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	6 mm ± 0.5 mm			
Size	50 x 50 cm standard size, 4m ² per box			
Colourway	4169002 Diffuse 4169008 Isolation 4169014 Contemplate 4169018 Regard	4169003 Solitude 4169009 Content 4169015 Harmoniu	4169005 Serene 4169011 Soothe 419016 Reserved	4169007 Transcribe 4169012 Retreat 4169017 Seclusion
		4169019 Patience	4169020 Secure	4169021 Deliberate
	4273001 Sapphire	4273002 Marine	4273003 Sailing	4273004 Pewter
	4273005 Lavender	4273007 Berry 4273008 Cranberry 4273006 Aubergine		
	4273009 Abyss	4273010 Harbour	4273011 Wave	4273012 Willow
	4273013 Fern	4273014 Olive	4273015 Amber	4273016 Sunburst
Method of laying	Non Directional Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

Interface®