

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Drawn Lines

Location	Heavy use for entrance and stairs in office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface LVT installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Luxury Vinyl Tiles	
Supplier	Interface
Product Reference	Drawn Lines
Туре	High performance luxury vinyl tile
Standard Backing	Sound Choice™ acoustic backing
BS EN 651 classifica	tion
Category	Heterogeneous luxury vinyl tile
Level of use class	Class 33 heavy commercial / 42 general light industrial
Total Thickness	4.5 mm ± 0.5 mm
Size	25 x 100 cm standard size
Colourway	A00902 Topaz A00903 Bronze A00904 Smokey Quartz A00905 Amber A00906 Aquamarine A00907 Onyx A00908 Silver A00909 Diamond A00910 Opal A00911 Amethyst
Method of laying	Ashlar, Herringbone Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

For Installation instructions, click <u>here</u> For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

