

## NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## **Employ Dimensions**

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Employ Dimensions
Туре	Tufted Patterned Level Loop Pile
Yarn	100% Solution Dyed Nylon
Standard Backing	CQuest™Bio
Backing Options	SONE® & ReCushion Bac
BS EN 1307 classifica	ation
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	5.5 mm ± 0.5 mm
Size	25 x 100 cm standard size, 5m <sup>2</sup> per box
Colourway	4271003 Connect 4271005 Time 4271004 Parallel 4271006 Scale   4271001 Volume 4271008 Measure 4271002 Surface 4271007 Line   4271010 Object 4271009 Segment
Method of laying	Ashlar, Herringbone Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

