



Equilibrium

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.		
Base	Please refer to Interface installation guide for details of suitability.		
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.		
Fabricated Underlay	Should be laid where required over existing timber bases.		
Carpet Tiles			
Manufacturer	Interface		
Product Reference	Equilibrium		
Type	Structured loop pile		
Yarn	100% Recycled Solution Dyed Nylon		
Standard Backing	CQuest™Bio		
BS EN 1307 classification			
Category	Type 1		
Level of use class	Heavy Contract, class 33		
Luxury rating class	LC2		
Total Thickness	7.3 mm ± 0.5 mm		
Size	50 x 50 cm - 4 m ² Box		
Colourway	1 190095 Consistency	1 190026 Contentment	1 190094 Continuity
	1 190096 Equality	1 190021 Equation	1 190028 Harmony
	1 190018 Mobility	1 190029 Moderation	1 190092 Persistence
	1 190023 Serenity	1 190022 Symmetry	1 190031 Uniformity
Method of laying	Ashlar, Monolithic, Quarter Turn. Install using TacTiles® for a glue-free installation		

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465

