

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Ice Breaker

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Ice Breaker			
Туре	Tufted Patterned Structured Loop Pile			
Yarn	100% Solution Dyed Nylon, contains recycled content			
Standard Backing	CQuest™Bio			
BS EN 1307 classific	ication			
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.6 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	4282009 Quarry 4282024 Pestle	4282006 Obsidian 4282021 Oatmeal 4282025 Peach	4282022 Mushroom 4282026 Pinkroot	4282004 Chalk 4282008 Siltstone 4282023 Amethyst 4282027 Sandstone 4282031 Malachite 4282035 Thistle
Method of laying	Non Directional Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

