



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

New Horizons II

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	New Horizons II			
Type	Level loop pile			
Yarn	100% Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	5.2 mm ± 0.5 mm			
Size	50 x 50 cm - 5 m ² Box			
Colourway	5581 Wheat	5582 Oak	5583 Nougat	5584 Chameleon
	5585 Pebbles	5586 Ash	5587 Silver	5588 Platin
	5589 Carbon	5590 Sky	5591 Marine	5592 Amaryllis
	5593 Steel	5594 Cobalt	5595 Navy	5596 Petrol
	5597 Palm	5598 Windsor		
Method of laying	Monolithic, Quarter Turn. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465