NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING 130 CARPET TILING

Off Line

N55Plus

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Off Line
Туре	Tufted Patterned Structured Loop Pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classifica	ation
Category	Туре 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC2
Total Thickness	7.1 mm ± 0.5 mm
Size	25 x 100 cm - 4 m ² Box
Colourway	7559001 Mushroom/Biscuit 7559002 Mushroom/Mustard 7559003 Sage/Biscuit 7559004 Sage/Canary 7559005 Pewter/Cloud 7559006 Pewter/Mandarin
	7559007 Pepper/Cloud 7559008 Pepper/Lime
Method of laying	Herringbone, Ashlar. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click <u>here</u> For Installation instructions, click <u>here</u> For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

