

## NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## On Line

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	On Line			
Туре	Tufted Patterned Structured Loop Pile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classific	ation			
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	$7.1 \text{ mm} \pm 0.5 \text{ mm}$			
Size	25 x 100 cm - 4 m <sup>2</sup> Box			
Colourway	7335001 Biscuit 7335005 Canary 7335009 Pepper 7335017 Forest 7335021 Dune 7335025 Pigeon	7335002 Mushroom 7335006 Cloud 7335010 Lime 7335018 Azure 7335022 Titanium 7335006 Aquamarine	7335003 Mustard 7335007 Pewter 7335015 Topaz 7335019 Lapis 7335023 Sable 7335027 Cobalt	7335004 Sage 7335008 Mandarin 7335016 Ink 7335020 Poppy 7335024 Granite 7335028 Magenta
Method of laying	Ashlar, Herringbone. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click <u>here</u>
For Installation instructions, click <u>here</u>
For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

Interface®