NBS



M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING 130 CARPET TILING

Output Loop

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Output Loop			
Туре	Level loop pile			
Yarn	100% Solution Dyed Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Туре 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	5.5 mm ± 0.5 mm			
Size	50 x 50 cm - 5 m ² Box 100 m ² PL			
Colourway	4219001 Sandstone 4219005 Dove 4219009 Mineral 4219013 Lime	4219002 Linen 4219006 Steel 42719010 Azure 4219014 Ivy	4219003 Pebble 4219007 Pewter 4219011 Teal 4219015 Tangerine	4219004 Chestnut 4219008 Charcoal 4219012 Sapphire 4219016 Paprika
Method of laying	Quarter Turn, Monolithic. Install using TacTiles [®] for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click <u>here</u> For Installation instructions, click <u>here</u> For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

