

Paver

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Paver			
Type	Tufted Patterned Structured Loop Tile			
Yarn	100% Recycled Solution Dyed Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.7 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway	8337001 Granite	8337002 Slate	8337003 Flint	8337004 Onyx
	8337200 Mushroom	8337201 Smoke	8337202 Shale	8337203 Forest
	8337204 Haze	8337205 Sage	8337206 Sand	8337207 Silver
Method of laying	Non Directional Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465