M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Embodied Beauty - Sashiko Stitch

NBS

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Embodied Beauty - Sashiko Stitch
Туре	Tufted Patterned Structured Loop Pile
Yarn	100% Solution Dyed Nylon, contains recycled content
Standard Backing	CQuest™Bio
BS EN 1307 classific	ation
Category	Туре 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC2
Total Thickness	6.4 mm ± 0.5 mm
Size	25 x 100 cm standard size
Colourway	9552001 Flint 9552002 Ash 9552003 Indigo 9552004 Jet 9552005 Poppy 9552006 Jadeite
Method of laying	Ashlar & Herringbone Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

Interface[®]