## **NS**SPlus

## M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING 130 CARPET TILING

## Look Both Ways - Step Aside

NBS

	7
Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Look Both Ways - Step Aside
Туре	Tapestry Tufted patterned structured tip sheared pile
Yarn	100% Solution Dyed Nylon contains recycled content
Standard Backing	CQuest™Bio
BS EN 1307 classific	ation
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC2
Total Thickness	7.3 mm ± 0.5 mm
Size	50 x 50 cm standard size
Colourway	9404001 Alba 9404002 Ash 9404003 Ebony 9404004 Coal
	9404005 Indigo 9404006 Jet
Method of laying	Ashlar, Brick and Monolithic. Install using TacTiles <sup>®</sup> for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

## **Interface**<sup>®</sup>