

## NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

## Look Both Ways - Step in Time

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
<b>Carpet Tiles</b>				
Manufacturer	Interface			
Product Reference	Look Both Ways - Step in Time			
Туре	Tapestry Tufted patterned structured tip sheared pile			
Yarn	100% Solution Dyed Nylon contains recycled content			
Standard Backing	CQuest™Bio			
BS EN 1307 classific	ation			
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC2			
Total Thickness	6.9 mm ± 0.5 mm			
Size	50 x 50 cm standard size			
Colourway		9403002 Ash 9403006 Jet	9403003 Ebony	9403004 Coal
Method of laying	Ashlar, Brick, Monolithic and Non Directional. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

