



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

The Scandinavian Collection

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	The Scandinavian Collection
Type	Microtufted loop pile
Yarn	100% Solution Dyed Nylon contains recycled content
Standard Backing	CQuest™Bio
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	4.4 mm ± 0.5 mm
Size	50 x 50 cm - 5 m ² Box
Colourway	1543001 Bergen 1543002 Helsinki 1543003 Reykjavik 1543004 Stockholm 1543006 Malmo 1543012 Copenhagen 1543013 Nordkapp 1543016 Hekla 1543033 Visby 1543034 Torshavn 1543035 Narvik 1543036 Kirkenes
Method of laying	Quarter Turn. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465