

M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING 130 CARPET TILING

Touch & Tones 102

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Touch & Tones II 102			
Туре	Structured loop pile			
Yarn	100% Recycled Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Туре 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC3			
Total Thickness	8.5 mm ± 0.5 mm			
Size	50 x 50 cm - 4 m2Box			
Colourway	4175070 Biscuit 4175074 Concrete 4175078 Olive 4175082 Blush	4175071 Mushroom 4175075 Stone 4175079 Forest 4175083 Gold	4175072 Coffee 4175076 Iron 4175080 Petrol 4175084 Garnet	4175073 Carbon 4175077 Anthracite 4175081 Sapphire 4175085 Terracotta
Method of laying	Monolithic. Install using TacTiles [®] for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click <u>here</u> For Installation instructions, click <u>here</u> For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

Interface[®]