



Touch & Tones 103

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	Should be laid where required over existing timber bases.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Touch & Tones II 103			
Type	Cut pile tufted			
Yarn	100% Recycled Nylon			
Standard Backing	CQuest™Bio			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC5			
Total Thickness	10.4 mm ± 0.5 mm			
Size	50 x 50 cm - 3 m2Box			
Colourway	4176045 Biscuit	4176046 Mushroom	4176047 Coffee	4176048 Carbon
	4176049 Concrete	4176050 Stone	4176051 Iron	4176052 Anthracite
	4176053 Olive	4176054 Forest	4176055 Petrol	4176056 Sapphire
	4176057 Blush	4176058 Gold	4176059 Garnet	4176060 Terracotta
Method of laying	Monolithic. Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465