

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Urban Retreat 102

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	Should be laid where required over existing timber bases.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Urban Retreat 102
Туре	Tapestry Tufted Patterned Structured Loop Pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classific	ation
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	$7.4 \text{ mm} \pm 0.5 \text{ mm}$
Size	$50 \times 50 \text{ cm} - 4 \text{ m}^2 \text{ Box}$
Colourway	7146004 Granite 7146002 Charcoal 7146003 Straw
	7146008 Ash 7146006 Stone 7146005 Flax
Method of laying	Non Directional, Quarter Turn. Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Carbon Neutral Floors. Every product carbon neutral. When you purchase any Interface products, we'll calculate your flooring's impact on global warming and ensure it's offset.

To see the BREEAM contribution click <u>here</u>
For Installation instructions, click <u>here</u>
For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

