

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Look Both Ways - Walk the Aisle

Location	Heavy use for entrance and stairs in office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface LVT installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Luxury Vinyl Tiles	
Supplier	Interface
Product Reference	Look Both Ways - Walk the Aisle
Туре	High performance luxury vinyl tile
Standard Backing	Sound Choice™ acoustic backing
BS EN 651 classifica	tion
Category	Heterogeneous luxury vinyl tile
Level of use class	Class 33 heavy commercial / 42 general light industrial
Total Thickness	4.5 mm ± 0.5 mm
Size	50 x 50 cm standard size
Colourway	A01301 Warm A01302 Pumice A01303 Cool Ash A01304 Carbon Ash
Method of laying	Monolithic, Ashlar, Brick, Quarter Turn & Non Directional

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

