

Works Flow

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.			
Base	Please refer to Interface installation guide for details of suitability.			
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.			
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.			
Carpet Tiles				
Manufacturer	Interface			
Product Reference	Works Flow			
Type	Tufted Patterned Structured Loop Pile			
Yarn	100% Solution Dyed Nylon			
Standard Backing	CQuest™Bio			
Backing Options	SONE® & ReCushion Bac			
BS EN 1307 classification				
Category	Type 1			
Level of use class	Heavy Contract, class 33			
Luxury rating class	LC1			
Total Thickness	6.6 mm ± 0.5 mm			
Size	50 x 50 cm standard size, 4m ² per box			
Colourway	4276001 Linen	4276002 Mink	4276003 Mocha	4276004 Pebble
	4276005 Charcoal	4276006 Black	4276007 Canary	4276008 Sunrise
	4276009 Aqua	4276010 Lime	4276011 Violet	4276012 Cobalt
Method of laying	Brick, Monolithic, Ashlar Install using TacTiles® for a glue-free installation			

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

Simply add our Cool Carpet service to your order to make your purchase carbon neutral.

To see the BREEAM contribution click [here](#) For Installation instructions, click [here](#) For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465