



NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Works Freestyle

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Works Freestyle
Type	Tufted Patterned Structured Loop Pile
Yarn	100% Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	7.2 mm ± 0.5 mm
Size	25 x 100 cm standard size, 5m ² per box
Colourway	4284001 Nickel 4284002 Slate 4284003 Iron 4284004 Smoke 4284005 Ice 4284006 Cloud 4284007 Pearl 4284008 Cotton
Method of laying	Ashlar & Herringbone Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

To see the BREEAM contribution click [here](#) For Installation instructions, click [here](#). For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465