

Northern Grain

Location	Heavy use for entrance and stairs in office, retail, hospitality, leisure and educational areas.		
Base	Please refer to Interface LVT installation guide for details of suitability.		
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.		
Luxury Vinyl Tiles			
Supplier	Interface		
Product Reference	Northern Grain		
Type	High performance luxury vinyl tile with Ceramor+ coating, PTV 36+ wet		
Standard Backing	Sound Choice™ acoustic backing		
BS EN 651 classification			
Category	Heterogeneous luxury vinyl tile		
Level of use class	Class 33 heavy commercial / 42 general light industrial		
Total Thickness	4.5 mm ± 0.5 mm		
Size	25 x 100 cm standard size		
Colourway	A02601 Glazed Oak	A02602 Chiffon Oak	A02603 Bare Oak
	A02604 Dried Oak	A02605 Nordic Wash	A02606 Antique Wash
	A02607 Dark Wash	A02608 Grey Wash	A02609 Aged Satin
	A02610 Natural Satin	A02611 Oak Satin	A02612 Dark Satin
Method of laying	Ashlar, Herringbone		

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are carbon neutral through its entire product lifecycle, as standard and at no extra cost, through the Interface Carbon Neutral Floors™ programme.

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465