

## Open Air 402

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.		
<b>Base</b>	Please refer to Interface installation guide for details of suitability.		
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.		
<b>Fabricated Underlay</b>	N/a. Carpet tiles to be adhered direct to the subfloor.		
<b>Carpet Tiles</b>			
<b>Manufacturer</b>	Interface		
<b>Product Reference</b>	Open Air 402		
<b>Type</b>	Tufted Patterned Structured Loop Pile		
<b>Yarn</b>	100% Recycled Solution Dyed Nylon		
<b>Standard Backing</b>	CQuest™Bio		
<b>BS EN 1307 classification</b>			
<b>Category</b>	Type 1		
<b>Level of use class</b>	Heavy Contract, class 33		
<b>Luxury rating class</b>	LC1		
<b>Total Thickness</b>	6.8 mm ± 0.5 mm		
<b>Size</b>	25 x 100 cm standard size		
<b>Colourway</b>	9624001 Black	9624002 Iron	9624003 Flannel
	9624004 Charcoal	9624005 Natural	9624006 Nickel
	9624007 Granite	9624008 Stone	9624009 Linen
<b>Method of laying</b>	Ashlar, Herringbone Install using TacTiles® for a glue-free installation		

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465