

## Open Air 403

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.		
<b>Base</b>	Please refer to Interface installation guide for details of suitability.		
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.		
<b>Fabricated Underlay</b>	N/a. Carpet tiles to be adhered direct to the subfloor.		
<b>Carpet Tiles</b>			
<b>Manufacturer</b>	Interface		
<b>Product Reference</b>	Open Air 403		
<b>Type</b>	Tufted Patterned Structured Loop Pile		
<b>Yarn</b>	100% Recycled Solution Dyed Nylon		
<b>Standard Backing</b>	CQuest™Bio		
<b>BS EN 1307 classification</b>			
<b>Category</b>	Type 1		
<b>Level of use class</b>	Heavy Contract, class 33		
<b>Luxury rating class</b>	LC1		
<b>Total Thickness</b>	6.7 mm ± 0.5 mm		
<b>Size</b>	50 x 50 cm standard size		
<b>Colourway</b>	9626001 Black	9626002 Iron	9626003 Flannel
	9626004 Charcoal	9626005 Natural	9626006 Nickel
	9626007 Granite	9626008 Stone	9626009 Linen
<b>Method of laying</b>	Non Directional Install using TacTiles® for a glue-free installation		

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465