

Open Air 404

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.		
Base	Please refer to Interface installation guide for details of suitability.		
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.		
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.		
Carpet Tiles			
Manufacturer	Interface		
Product Reference	Open Air 404		
Type	Tufted Patterned Structured Loop Pile		
Yarn	100% Recycled Solution Dyed Nylon		
Standard Backing	CQuest™Bio		
BS EN 1307 classification			
Category	Type 1		
Level of use class	Heavy Contract, class 33		
Luxury rating class	LC1		
Total Thickness	6.7 mm ± 0.5 mm		
Size	50 x 50 cm standard size		
Colourway	9625001 Black	9625002 Iron	9625003 Flannel
	9625004 Charcoal	9625005 Natural	9625006 Nickel
	9625007 Granite	9625008 Stone	9625009 Linen
Method of laying	Non Directional Install using TacTiles® for a glue-free installation		

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465