

Open Air 404 Transition

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.		
Base	Please refer to Interface installation guide for details of suitability.		
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.		
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.		
Carpet Tiles			
Manufacturer	Interface		
Product Reference	Open Air 404 Transition		
Type	Tufted Patterned Structured Loop Pile		
Yarn	100% Recycled Solution Dyed Nylon		
Standard Backing	CQuest™Bio		
BS EN 1307 classification			
Category	Type 1		
Level of use class	Heavy Contract, class 33		
Luxury rating class	LC1		
Total Thickness	6.9 mm ± 0.5 mm		
Size	50 x 50 cm standard size		
Colourway	9706001 Nickel/Pearl	9706002 Nickel/Rust	9706003 Nickel/Clementine
	9706004 Nickel/Maize	9706005 Nickel/Moss	9706006 Nickel/Teal
	9706007 Nickel/Caribbean	9706008 Nickel/Cobalt	
Method of laying	Non Directional Install using TacTiles® for a glue-free installation		

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465