

## Overedge

<b>Location</b>	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
<b>Base</b>	Please refer to Interface installation guide for details of suitability.
<b>Preparation</b>	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
<b>Fabricated Underlay</b>	N/a. Carpet tiles to be adhered direct to the subfloor.
<b>Carpet Tiles</b>	
<b>Manufacturer</b>	Interface
<b>Product Reference</b>	Overedge
<b>Type</b>	Tufted Patterned Shag Cut Tile
<b>Yarn</b>	100% Recycled Solution Dyed Nylon
<b>Standard Backing</b>	CQuest™Bio
<b>BS EN 1307 classification</b>	
<b>Category</b>	Type 1
<b>Level of use class</b>	General Contract, class 32
<b>Luxury rating class</b>	LC5
<b>Total Thickness</b>	11.6 mm ± 0.5 mm
<b>Size</b>	25 x 100 cm standard size
<b>Colourway</b>	9271001 B&W Overedge
<b>Method of laying</b>	Ashlar & Herringbone Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465