

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Past Forward - Retrospec

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Past Forward - Retrospec
Туре	Tapestry Tufted Patterned Structured Loop Tile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classification	
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC2
Total Thickness	8.5 mm ± 0.5 mm
Size	50 x 50 cm standard size
Colourway	9958001 Royal 9958002 Olive 9958003 Emerald
	9958004 Terracotta
Method of laying	Non Directional
	Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click <u>here</u>
For Installation instructions, click <u>here</u>
For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

