

M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING 130 CARPET TILING

Portmanteau - PM19

NBS

	T
Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Portmanteau - PM19
Туре	Tapestry Tufted Patterned Structured Loop Pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classific	ation
Category	Type 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC3
Total Thickness	9.7 mm ± 0.5 mm
Size	50 x 100 cm standard size
Colourway	7968001 Rosewood 7968002 Cobalt 7968003 Berry 7968004 Honey 7968005 Ebony & Ivory 7968005 Ebony & Ivory
Method of laying	Ashlar & Herringbone Install using TacTiles® for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities). All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click <u>here</u> For Installation instructions, click <u>here</u> For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

Interface[®]



M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING 130 CARPET TILING

Portmanteau - PM39

NBS

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Portmanteau - PM39
Туре	Tapestry Tufted Patterned Structured Loop Pile
Yarn	100% Recycled Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classific	ation
Category	Туре 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC2
Total Thickness	9.2 mm ± 0.5 mm
Size	50 x 100 cm standard size
Colourway	8063001 Ebony & Ivory 8063002 Butterscotch 8063003 Pistachio 8063004 Sage 8063005 Denim
Method of laying	Ashlar & Herringbone Install using TacTiles [®] for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities). All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click <u>here</u> For Installation instructions, click <u>here</u> For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

Interface[®]



M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING 130 CARPET TILING

Portmanteau - PM49

NBS

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.	
Base	Please refer to Interface installation guide for details of suitability.	
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.	
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.	
Carpet Tiles		
Manufacturer	Interface	
Product Reference	Portmanteau - PM49	
Туре	Tapestry Tufted Patterned Structured Loop Pile	
Yarn	100% Recycled Solution Dyed Nylon	
Standard Backing	CQuest™Bio	
BS EN 1307 classification		
Category	Туре 1	
Level of use class	Heavy Contract, class 33	
Luxury rating class	LC3	
Total Thickness	9.5 mm ± 0.5 mm	
Size	50 x 100 cm standard size	
Colourway	8064001 Ecru 8064002 Garden Stone	
Method of laying	Ashlar & Herringbone Install using TacTiles® for a glue-free installation	

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities). All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click <u>here</u> For Installation instructions, click <u>here</u> For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

Interface[®]