

## Upon Common Ground - Dry Bark

|                                  |   |                            |                           |
|----------------------------------|---|----------------------------|---------------------------|
| <b>Location</b>                  | Heavy use areas. Office, retail, hospitality, leisure and educational areas.                              |                            |                           |
| <b>Base</b>                      | Please refer to Interface installation guide for details of suitability.                                  |                            |                           |
| <b>Preparation</b>               | Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. |                            |                           |
| <b>Fabricated Underlay</b>       | N/a. Carpet tiles to be adhered direct to the subfloor.   |                            |                           |
| <b>Carpet Tiles</b>              |   |                            |                           |
| <b>Manufacturer</b>              | Interface   |                            |                           |
| <b>Product Reference</b>         | Upon Common Ground - Dry Bark   |                            |                           |
| <b>Type</b>                      | Tufted Patterned Structured Loop Tile   |                            |                           |
| <b>Yarn</b>                      | 100% Recycled Solution Dyed Nylon   |                            |                           |
| <b>Standard Backing</b>          | CQuest™Bio  |                            |                           |
| <b>BS EN 1307 classification</b> |   |                            |                           |
| <b>Category</b>                  | Type 1  |                            |                           |
| <b>Level of use class</b>        | Heavy Contract, class 33  |                            |                           |
| <b>Luxury rating class</b>       | LC2   |                            |                           |
| <b>Total Thickness</b>           | 7.6 mm ± 0.5 mm   |                            |                           |
| <b>Size</b>                      | 25 x 100 cm standard size   |                            |                           |
| <b>Colourway</b>                 | 2529001 Desert Neutral  | 2529002 Desert Sands       | 2529003 Saltwater Neutral |
|                                  | 2529004 Saltwater Depth   | 2529005 Rainforest Neutral | 2529006 Rainforest Canopy |
|                                  | 2529007 Freshwater Neutral  | 2529008 Freshwater Gorge   | 2529009 Spinifex Neutral  |
|                                  | 2529010 Spinifex Grass  |                            |                           |
| <b>Method of laying</b>          | Ashlar<br>Install using TacTiles® for a glue-free installation  |                            |                           |

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click [here](#)

For Installation instructions, click [here](#)

For Maintenance instructions, click [here](#)

To obtain samples please call 0800 313 4465