**NS**SPlus

M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING / SHEETING 130 CARPET TILING

## **Upon Common Ground - Escarpment**

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.		
Base	Please refer to Interface installation guide for details of suitability.		
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.		
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.		
Carpet Tiles			
Manufacturer	Interface		
Product Reference	Upon Common Ground - Escarpment		
Туре	Tufted Patterned Structured Loop Tile		
Yarn	100% Recycled Solution Dyed Nylon		
Standard Backing	CQuest™Bio		
BS EN 1307 classification			
Category	Туре 1		
Level of use class	Heavy Contract, class 33		
Luxury rating class	LC1		
Total Thickness	7.0 mm ± 0.5 mm		
Size	50 x 50 cm standard size		
Colourway	2525001 Desert Shrub	2525002 Desert Sands	2525003 Desert Neutral
	2525004 Saltwater Depth	2525005 Saltwater Cliff	2525006 Saltwater Neutral
	2525007 Rainforest Floor	2525008 Rainforest Canopy	2525009 Rainforest Neutral
	2525010 Freshwater Lomandra	2525011 Freshwater Gorge	2525012 Freshwater Neutral
	2525013 Spinifex Grass	2525014 Spinifex Dirt	2525015 Spinifex Neutral
Method of laying	Ashlar Install using TacTiles <sup>®</sup> for a glue-free installation		

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click <u>here</u> For Installation instructions, click <u>here</u> For Maintenance instructions, click <u>here</u>

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

## **Interface**<sup>®</sup>