

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Works Effect

| Location | Heavy use areas. Office, retail, hospitality, leisure and educational areas. |
|----------------------|---|
| Base | Please refer to Interface installation guide for details of suitability. |
| Preparation | Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. |
| Fabricated Underlay | N/a. Carpet tiles to be adhered direct to the subfloor. |
| Carpet Tiles | |
| Manufacturer | Interface |
| Product Reference | Works Effect |
| Туре | Tufted Patterned Structured Loop Pile |
| Yarn | 100% Solution Dyed Nylon |
| Standard Backing | CQuest™Bio |
| BS EN 1307 classific | ation |
| Category | Type 1 |
| Level of use class | Heavy Contract, class 33 |
| Luxury rating class | LC1 |
| Total Thickness | 7.0 mm ± 0.5 mm |
| Size | 50 x 50 cm standard size |
| Colourway | 4311001 Lakeside 4311002 Cactus 4311003 Honey 4311004 Haze 4311005 Canyon 4311006 Mint 4311007 Shell 4311008 Adrift 4311009 Ebony |
| Method of laying | Non-Directional Install using TacTiles® for a glue-free installation |

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

