

NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ **CARPET TILING**/ SHEETING 130 CARPET TILING

Works Element

| Location | Heavy use areas. Office, retail, hospitality, leisure and educational areas. |
|----------------------|---|
| Base | Please refer to Interface installation guide for details of suitability. |
| Preparation | Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards. |
| Fabricated Underlay | N/a. Carpet tiles to be adhered direct to the subfloor. |
| Carpet Tiles | |
| Manufacturer | Interface |
| Product Reference | Works Element |
| Туре | Tufted Patterned Structured Loop Pile |
| Yarn | 100% Solution Dyed Nylon |
| Standard Backing | CQuest™Bio |
| BS EN 1307 classific | ation |
| Category | Type 1 |
| Level of use class | Heavy Contract, class 33 |
| Luxury rating class | LC1 |
| Total Thickness | 6.4 mm ± 0.5 mm |
| Size | 50 x 50 cm standard size |
| Colourway | 4310001 Lakeside 4310002 Cactus 4310003 Honey 4310004 Haze 4310005 Canyon 4310006 Mint 4310007 Shell 4310008 Adrift 4310009 Ebony |
| Method of laying | Non-Directional Install using TacTiles® for a glue-free installation |

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities).

All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

