NBS

M50 RUBBER/ PLASTICS/ CORK/ LINO/ CARPET TILING/ SHEETING 130 CARPET TILING

Works Sense

NSSPlus

Location	Heavy use areas. Office, retail, hospitality, leisure and educational areas.
Base	Please refer to Interface installation guide for details of suitability.
Preparation	Subfloors should be prepared in accordance with BS 5325 or corresponding National and European Standards.
Fabricated Underlay	N/a. Carpet tiles to be adhered direct to the subfloor.
Carpet Tiles	
Manufacturer	Interface
Product Reference	Works Sense
Туре	Tufted Patterned Structured Loop Pile
Yarn	100% Solution Dyed Nylon
Standard Backing	CQuest™Bio
BS EN 1307 classifica	ation
Category	Туре 1
Level of use class	Heavy Contract, class 33
Luxury rating class	LC1
Total Thickness	6.6 mm ± 0.5 mm
Size	50 x 50 cm standard size
Colourway	4312001 Lakeside4312002 Cactus4312003 Honey4312004 Haze4312005 Canyon4312006 Mint4312007 Shell4312008 Adrift4312009 Ebony4312009 Ebony4312008 Adrift
Method of laying	Ashlar & Brick Install using TacTiles [®] for a glue-free installation

Use the Interface ReEntry service to take away existing Interface tiles which will be cleaned and re purposed through our partners (Registered charities). All Interface products are Carbon Neutral through Carbon Neutral Floors™

To see the BREEAM contribution click here For Installation instructions, click here For Maintenance instructions, click here

To obtain samples please call 0800 313 4465

Interface Europe Ltd, 10th Floor, The Colmore Building, 20 Colmore Circus, Queensway, Birmingham, B4 6AT Customer Services Tel: 0800 313 4465, Email: enquiries@interface.com www.interface.com

Interface[®]